

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application.

1. (Original) A method of replicating data objects from a source system to a target system, comprising:

creating an electronic data element comprising a first field having an identifier

and a second field having a state of the identifier, wherein the state of the identifier may be set to:

a) a first state, in which said electronic data element may be

accessed by one or more data object processing operations

and whereby said identifier is assignable to one or more data objects,

b) a second state, in which said electronic data element may not be

accessed by one or more data object processing operations

and whereby said identifier is assignable to one or more data objects, or

c) a third state, in which said electronic data element may not be

accessed by one or more data object processing operations

and whereby said identifier is not assignable to one or more data objects;

assigning the identifier to one or more data objects;

assigning a state to the identifier; and
replicating the one or more assigned data objects from the source system to the
target system if the state of the identifier is the third state.

2. (Original) The method of claim 1, further comprising storing the one or more assigned data objects prior to replicating the one or more assigned data objects.
3. (Original) The method of claim 2, further comprising setting the state of the second field of the electronic data element to the second state.
4. (Original) The method of claim 3, further comprising, upon a commit of the storing of the one or more data objects, the state of the second field of the electronic data element is set to the third state.
5. (Original) A system for avoiding data loss in a data object replication process, comprising:
 - a memory; and
 - a microprocessor coupled to the memory and programmed to:
 - create an electronic data element comprising a first field having an identifier and a second field having a state of the identifier, wherein the state of the identifier may be set to:
 - a) a first state, in which said electronic data element may be accessed by one or more data object processing

operations and whereby said identifier is assignable
to one or more data objects,

- b) a second state, in which said electronic data element may
not be accessed by one or more data object
processing operations and whereby said identifier is
assignable to one or more data objects, or
- c) a third state, in which said electronic data element may
not be accessed by one or more data object
processing operations and whereby said identifier is
not assignable to one or more data objects;

assign the identifier to one or more data objects;

assign a state to the identifier; and

replicate the one or more assigned data objects from the source system to
the target system if the state of the identifier is the third state.

6. (Original) The system of claim 5, wherein the microprocessor is further
programmed to store the one or more assigned data objects prior to replicating the one
or more assigned data objects.

7. (Original) The system of claim 6, wherein the microprocessor is further
programmed to set the state of the second field of the electronic data element to the
second state.

8. (Original) The system of claim 7, wherein the microprocessor is further programmed to, upon a commit of the storing of the one or more data objects, the state of the second field of the electronic data element is set to the third state.

Please add the following new claim 9:

9. (New) A system for replicating data objects from a source system to a target system, the system comprising:

means for creating an electronic data element comprising a first field having an identifier and a second field having a state of the identifier, wherein the state of the identifier may be set to:

- a) a first state, in which said electronic data element may be accessed by one or more data object processing operations and whereby said identifier is assignable to one or more data objects,
- b) a second state, in which said electronic data element may not be accessed by one or more data object processing operations and whereby said identifier is assignable to one or more data objects, or
- c) a third state, in which said electronic data element may not be accessed by one or more data object processing operations and whereby said identifier is not assignable to one or more data objects;

means for assigning the identifier to one or more data objects;

means for assigning a state to the identifier; and

means for replicating the one or more assigned data objects from the source
system to the target system if the state of the identifier is the third state.